

**New!**



# SIGNODE LB-2000™

**Plastic strapping machine**

***Jam-resistant  
technology***

***Up to 52  
straps per  
minute***

***Maintenance-  
free***

**A** worldwide leader in the development of superior strapping systems since 1913, Signode introduces the LB-2000™ with the highest available speeds, most reliable performance and lowest maintenance operation of any general-duty strapping machine on the market today.



**SIGNODE®**

# SIGNODE LB-2000™ Plastic strapping machine

## A new generation of strapping systems from Signode

### Jam-resistant technology

The LB-2000™ offers the most jam-resistant technology available in any plastic strapping machine today.

### Unequaled speed

Cycling up to 52 straps per minute, the LB-2000 is the fastest standard machine in its class.

### Automatic refeed

In the event of a non-completed feed, the machine automatically corrects itself.

### Lubrication-free operation

The LB-2000's self-lubricating design provides excellent durability and maintenance-free operation.

### Variable tension

Tension is easy to adjust using a single tension dial. Once the desired maximum tension level is set, you can change to low tension and back again with the simple flick of a switch.

### Fully accessible strap path

Machine and strapping head covers are easily removed or fully opened, making the strapping head completely accessible.

### Portable design

Four heavy-duty swivel casters (two locking), robust machine construction, compact design with space conserving dispenser and 110 volt electrical requirements simplify machine relocation and set up.

### No adjustments

This is the only strapping machine available with no internal adjustments.

### Strap size

Easy to change from 5mm to 6mm polypropylene strapping. No special parts are needed for the conversion.

### Made in the U.S.A.

## Options

### Electric photo eye

Easily attached to the LB-2000, the photo eye triggers automatic strap cycling. A switch on the photo eye enables you to select one strap, continuous strapping or no straps.

### Remote cycle switch

The portable cycle switch with heavy-duty magnetic backing can be positioned anywhere on or near the machine for the most convenient strap cycle activation.



**SIGNODE®**

180 Hastings Drive  
Buffalo Grove, Illinois 60089  
1-800-526-1948

## Contrax® plastic strapping



Enhance the quality and performance of your LB-2000 strapping machine with Signode Contrax® polypropylene strapping.

- Consistent width and gauge control
- Smooth, uniform surface
- Resists splitting
- Recovers when elongated
- Available in various break strengths
- Recyclable (ask about Signode's recycling program)

## LB-2000 Specifications

**Production rate:** Up to 52 straps per minute

**Chute size:** See illustration below

**Minimum package size:** 50mm x 25mm (2" x 1")

**Strap tension:** Adjustable up to 60 lbs.

**Machine dimensions:** 840mm W x 510mm L x 1400mm H (33" W x 20" L x 55" H), maximum height

**Tabletop height:** 865mm (34")

**Electrical requirements:** 110 volt, 60Hz

**Shipping weight:** 540 lbs.

### Chute dimensions:

	Small chute		Large chute	
	mm	inches	mm	inches
<b>A</b>	600	23.75	730	28.75
<b>B</b>	420	16.75	420	16.75

